IN THE CLAIMS:

Please amend claims 1-12 as follows. Please cancel claims 13-17 without prejudice or disclaimer. Please add new claims 18 and 19.

1. (Currently Amended) A method for transferring information~~, such as a new service, or at least information about the new service,~~ by a server~~(14)~~ to a mobile terminal~~(MS)~~ in a predetermined area of a packet-switched network ~~(HPLMN, VPLMN)~~ comprising a plurality of support nodes~~(SGSN, GGSN);~~

~~characterized by~~ the method comprising the steps of:

associating at least one identifier~~(IMSI)~~ of the mobile terminal~~(MS)~~ with a Packet Data Protocol address, or PDP address, of the same mobile terminal;

operationally connecting the server~~(14)~~ and all support nodes~~(SGSN, GGSN)~~ in said predetermined area to an intelligent network node~~(SCP)~~;

informing~~(2-6)~~ the intelligent network node ~~(SCP)~~ about the identifier~~(IMSI)~~ and the current PDP address of the mobile terminal~~(MS)~~; and

using the PDP address stored in the intelligent network node~~(SCP)~~ for routing~~(2-10 ... 2-14)~~ said information to the mobile terminal~~(MS)~~.

2. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the using step comprises the following steps:

before transferring said information to the mobile terminal ~~(MS)~~, the server ~~(14)~~ sends to the intelligent network node ~~(SCP)~~ an inquiry ~~(2-10)~~ requesting the PDP address of the mobile terminal ~~(MS)~~; and

in response to the inquiry ~~(2-10)~~, the intelligent network node ~~(SCP)~~ sends to the server ~~(14)~~ the PDP address of the mobile terminal ~~(MS)~~;

whereby the server ~~(14)~~ is able to communicate ~~(2-14)~~ with the mobile terminal ~~(MS)~~ using the PDP address indicated by the intelligent network node ~~(SCP)~~.

3. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the using step comprises the following steps:

the server ~~(14)~~ sends ~~(2-10')~~ the information to the intelligent network node ~~(SCP)~~; and

the intelligent network node ~~(SCP)~~ sends ~~(2-12')~~ said information to the mobile terminal ~~(MS)~~ without disclosing the mobile terminal's PDP address to the server ~~(14)~~.

4. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the using step comprises the following steps:

the intelligent network node ~~(SCP)~~ stores, in addition to the PDP address, an address of at least one server ~~(14)~~; and

upon receiving the current PDP address of the mobile terminal ~~(MS)~~, the intelligent network node ~~(SCP)~~ sends the current PDP address to said at least one server ~~(14)~~;

whereby the server ~~(14)~~ is able to communicate with the mobile terminal ~~(MS)~~ without a separate inquiry.

5. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the address of the intelligent network node~~(SCP)~~ is stored with the subscription data related to the mobile terminal~~(MS)~~.

6. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the step of informing the intelligent network node~~(SCP)~~ is responsive to a detected establishment and/or change in the PDP address.

7. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein the step of informing the intelligent network node~~(SCP)~~ is performed by a Serving GPRS Support Node~~(SGSN)~~ having Service Switching Point~~(SSP)~~ functionality.

8. (Currently Amended) A method according to claim 1, ~~characterized in that~~ wherein said packet-switched network~~(HPLMN, VPLMN)~~ communicates with said mobile terminal~~(MS)~~ over a radio interface.

9. (Currently Amended) A Service Control Point~~(SCP)~~, ~~characterized in that,~~ wherein

for transferring information~~, such as a new service, or at least information about the new service,~~ by a server~~(14)~~ to a mobile terminal~~(MS)~~ having at least one identifier ~~(IMSI)~~and a PDP address, in a packet-switched network~~(HPLMN, VPLMN)~~ comprising a plurality of support nodes~~(SGSN, GGSN)~~, the Service Control Point~~(SCP)~~ is

operationally connected to the packet-switched network~~(HPLMN, VPLMN)~~ and the serve ~~(14)~~;

adapted to store said at least one identifier~~(IMSI)~~ and the PDP address of the mobile terminal~~(MS)~~ in response to a first message~~(2-6)~~ originating from the packet-switched network; and

adapted to support said transferring of information by a server~~(14)~~.

10. (Currently Amended) A Service Control Point~~(SCP)~~ according to claim 9, ~~characterized in that~~ wherein the Service Control Point~~(SCP)~~ is adapted to receive a second message~~(2-10)~~ from the server~~(14)~~ and to respond to the second message~~(2-10)~~ by sending~~(2-12)~~ to the server ~~(14)~~ the PDP address of the mobile terminal~~(MS)~~.

11. (Currently Amended) A Service Control Point~~(SCP)~~ according to claim 9, ~~characterized in that~~ wherein the Service Control Point~~(SCP)~~ is adapted to receive from

the server~~(14)~~ a second message~~(2-10')~~ comprising said information, and to respond to the second message by sending~~(2-12')~~ said information to the mobile terminal~~(MS)~~.

12. (Currently Amended) A Service Control Point~~(SCP)~~ according to claim 9, ~~characterized in that~~ wherein the Service Control Point~~(SCP)~~ is adapted

to store, in addition to the PDP address, an address of at least one server ~~(14)~~; and

upon receiving the current PDP address of the mobile terminal ~~(MS)~~, to send the current PDP address to said at least one server ~~(14)~~.

Claims 13-17 (Cancelled).

18. (New) A method according to claim 1, wherein the transferred information conveys a new service, or at least information about the new service.

19. (New) A Service Control Point according to claim 9, wherein the transferred information conveys a new service, or at least information about the new service.